

PCTWORLD INTELLECTUAL PRO
International

INTERNATIONAL APPLICATION PUBLISHED UNDER

WO 9607317A1

(51) International Patent Classification ⁶ : A01K 23/00	A1	(11) International Publication Number: WO 96/07317
		(43) International Publication Date: 14 March 1996 (14.03.96)

(21) International Application Number: PCT/GB95/02033

(22) International Filing Date: 29 August 1995 (29.08.95)

(30) Priority Data:
9417744.1 3 September 1994 (03.09.94) GB(71)(72) Applicant and Inventor: LANGLEY, John, Charles, Mark
[GB/GB]; 5 Fettes Row, Edinburgh EH3 6SF (GB).(74) Agents: McCALLUM, William, Potter et al.; Cruikshank &
Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE
(GB).(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH,
CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE,
KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,
SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent
(AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW,
SD, SZ, UG).


Published

With international search report.

(54) Title: DOG FAECES COLLECTOR

(57) Abstract

The present invention relates to an animal faeces collector device (1). The device comprises a collapsible elongate handle (8) provided at a distal end thereof with a receptacle (10). The receptacle (10) has an upwardly facing deposition surface (16) in a deployed condition of the device (1) for receiving a faecal deposit (32) thereon. The elongate handle (8) is formed and arranged so as to be in a substantially highly compact pocketable form in a collapsed state of the device, and to be deployable by, for example, inflation to a substantially self-supporting state in a deployed state of the device (1).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

DOG FAECES COLLECTOR

The present invention relates to a device for catching and containing dog faeces.

Animals are in general not particular about where they
5 defecate. The streets, parks and pavements of towns
everywhere are littered with, especially, dog excreta. It
is unsightly, unhygienic, inconvenient and in the case of
canine animals can harbour dangerous diseases such as
toxocara which affects humans. Devices for the receiving
10 and disposal of animal, particularly dog, faeces have been
proposed previously and have been disclosed in for example
US 4466647 (Spevak), US 3977422 (Cabaluna); US 4003595
(Fado) and G 2218896 (Yoshioka). Such devices have proved
to be unsatisfactory for a variety of reasons including
15 bulkiness; complexity of use; risk of faecal matter
contamination; expense or simply that they are not
practicable for use by dogs and their owners.

It is an object of the present invention to provide a device
that can be used by dog owners in such a way as to avoid or
20 minimise one or more of the above disadvantages.

The present invention provides an animal faeces collector
device comprising a collapsible elongate handle means
provided at a distal end thereof with a receptacle having an
upwardly facing deposition surface in a deployed condition
25 of the device for receiving a faecal deposit thereon, said
elongate handle means being formed and arranged so as to be
collapsible into a highly compact pocketable form in a
collapsed state of the device, and to be deployable to a
substantially self-supporting state in a deployed state of
30 the device.

Preferably said receptacle for receiving faecal deposits is
itself deployable from a substantially collapsed state to a
substantially self supporting deployed state defining said
upwardly facing deposition surface in said deployed state of
35 the device for receiving faecal deposits thereon whereby in

use of said device, said receptacle may be deployed and positioned under a dog in the defecating position for the sanitary collection of faecal deposits.

Such devices of the present invention are based upon inter alia a recognition, for the first time, that the receptacle and the handle means can be made to be extremely lightweight with very limited rigidity just sufficient to be self supporting and to position and direct the empty receptacle more or less accurately relative to the animal's anus. Once a faecal deposit has been made on the receptacle the latter will become considerably heavier. At this stage though it is no longer necessary to have the same directional control over the receptacle, and it is sufficient simply to be able to carry this in a convenient manner. This can though be achieved with a very lightweight handle and/or other support means which have sufficient tensile strength - which can be achieved with a much lighter construction than can a rigid handle means relying on the rigidity thereof (e.g. in leverage) to carry the same weight. Thus such devices of the invention can be made with a much more compact and thus more readily pocketable construction than can previously known devices.

In another respect the present invention provides an inflatable animal faeces collector device which device comprises a structure deployable from a first highly compact pocketable collapsed state to a second substantially self-supporting state defining and supporting a receptacle having an upwardly facing deposition surface in a deployed condition for receiving a faecal deposit thereon, said device having coupling means formed and arranged for coupling with a generally rigid elongate handle means for supporting said device at a distal end thereof, whereby in use said device may be inflated, coupled with a said more or less rigid elongate handle means and said receptacle positioned under a dog in the defecating position for the collection of faecal deposits.

Thus with collector devices according to the present invention dog faeces may be collected, contained and disposed of in a simple, hygienic and convenient manner.

Preferably the device in both aspects of the invention
5 includes receptacle security means for safeguarding the contents of a loaded receptacle during transfer of the device to a disposal station. Desirably said receptacle security means are remotely operable. Suitable security means may comprise a closure means such as a cover or,
10 especially in the case of a substantially flexible sheet material receptacle, a drawstring or like means for drawing in together the rim or support means of the receptacle over the contents thereof. Preferably said rim of the receptacle is provided with a support means formed and arranged to be
15 substantially self-supporting and to support said receptacle in an open condition in said deployed state of the device, said receptacle support means being formed and arranged with said handle means so as to be collapsible together into a substantially highly compact pocketable form in said
20 collapsed state of the device.

Preferably said collapsible elongate handle means and said receptacle support means of said collector device are formed and arranged so as to be inflatable from said collapsed state to said substantially self-supporting state, such that
25 the whole collector device is deployable by inflation.

Alternatively though only said receptacle support means is inflatable and said elongate handle means is in the form of a lightweight at least slightly rigid member when in said deployed state for supporting at a distal end thereof the
30 empty receptacle. Said lightweight member may thus be formed and arranged so as to be, for example, telescopically and/or hingedly, collapsible to a greater or lesser extent. Various lightweight members having sufficient rigidity to support themselves and an empty lightweight receptacle may
35 be used such as for example a composite or segmented elongate member comprising a plurality of discrete elongate portions interconnected generally end-to-end and formed and

arranged for articulation with respect to an adjacent portion. Preferably the length of each respective portion increases in a direction away from said receptacle and such that at each interconnection the longer of two adjacent portions extends partly under the underside of the adjacent shorter portion so as to provide a cantilevered support thereto and such that the member may be folded out from a collapsed state to a self-supporting state. Alternatively said lightweight member may comprise a plurality of portions telescopically interconnected. Desirably said lightweight members are made from suitably stiff lightweight materials such as sheet plastics or laminated paper/card strips, which may conveniently have a channel form in order to provide increased stiffness for a given weight of construction.

15 In another respect the present invention provides an inflatable animal faeces collector device which device comprises a structure deployable from a collapsed state to a substantially self supporting state defining an elongate handle means for supporting at a distal end thereof, a receptacle having an upwardly facing deposition surface in a deployed condition for receiving a faecal deposit thereon. Preferably said inflatable device is provided with remotely operable closure means formed and arranged for enclosing, in use, faecal deposits within said receptacle, whereby in use said device may be inflated and said receptacle positioned under a dog in the defecating position for the collection of faecal deposits and said closure means operated so as to substantially cover over the contents thereof and seal them inside so that they may be safely and hygienically disposed of.

Preferably said elongate handle means, and desirably said receptacle support means, are formed and arranged so as to be substantially flexible for coilable rolling up into said highly compact pocketable form. Alternatively said elongate handle means, and desirably said receptacle support means, are formed and arranged so as to be substantially flexible for folding up, for example in a concertina type

arrangement, into said highly compact pocketable form. Desirably there is provided releasable means on the device e.g. an adhesive strip for retaining said device in said substantially highly compact pocketable form prior to use.

- 5 Preferably there is used in the construction of the inflatable receptacle or the inflatable device, a light, flexible, waterproof material such as a plastics sheet material for instance polyvinylchloride, polyamide, polyalkene e.g. polyethylene, especially high density
10 polyethylene. Alternatively though there may be used a water resistant paper e.g. a waxed paper. In accordance with the present invention there may be provided such a device which is highly pocketable weighing as little as from 15 to 30g, e.g. about 20g, and having a size of as little as
15 around 4 x 4 x 3 cm when collapsed and readily extending to a handle length of around 60 cm when deployed with a receptacle capacity which may readily be made so as to be up to around 3/4 of a litre or more.

- Desirably there is used a bio-degradable material to
20 facilitate environmentally acceptable disposal of the closed receptacle with the faecal matter contained therein. Conveniently said material may be provided with a deodorizer, preferably a moisture activated deodorizer, to eliminate as far as possible noxious odours. The material
25 may be provided with marking to advertise the device's name (or other products) or provided with luminous and/or reflective markings for increased safety in use after dark.

- In the case of an inflatable elongate handle means or receptacle support means of the device, this may be deployed
30 into said self-supporting state by a user (dog owner), blowing into a compartment(s) in the device providing the structural support for the handle means or the receptacle/support means via a suitable, generally non-return, valve means. Alternatively there may be provided a
35 small gas supply means such as a cartridge or cylinder filled with compressed gas formed and arranged upon

actuation thereof to inflate said inflatable handle means and/or such receptacle support means of the device via a said suitable non-return valve. Conveniently said gas supply means when connected to said device for the inflation thereof itself may be used to act as a said "non-return valve" thus negating the requirement for a separate non-return valve to be provided on the device.

In use of the device and upon collection of a faecal deposit, said gas supply means may be removed from the device so as to permit the device to deflate and be disposed of. In the case of the inflatable device said valve is preferably positioned on said elongate handle at the proximal, hand grip, end thereof. Said valve may be simply removable so as to allow a said inflated device/receptacle to deflate and resume a substantially compact form for disposal purposes. Alternatively deflation may be achieved by providing the valve means with a pressure release position and/or providing a separate pressure relief valve.

Preferably the elongate handle means and/or said receptacle support means of the collector device is formed and arranged so that in its collapsed state, it can be folded or desirably rolled up into a small discreet package that may be conveniently kept in the dog owner's pocket or bag until such time as it is required. Where said device is to be rolled up, said elongate handle means may be provided with an automatic coiling mechanism such as a resiliently deformable plastics strip which in a normal rest position tends to adopt a substantially coiled form.

In the case of a device of the invention with an inflatable elongate handle means, there may be provided connector means, spaced apart on said inflatable elongate handle means, formed and arranged for releasable connection with an elongate, more or less, rigid additional support element, such as a walking stick, in a deployed state of said inflatable handle means for providing a greater degree of support for said inflatable handle means and/or said

receptacle in use thereof, for example in windy conditions.

In the case of a device of the invention which comprises an inflatable receptacle support means provided with a coupling means for a generally rigid elongate handle means, said
5 coupling means may conveniently comprise a socket formed and arranged for releasable connection with the end of an elongate, more or less, rigid support member such as a walking stick.

Preferably in both aspects of the present invention said
10 elongate handle means and said deposition surface are angled towards each other so that when said deposition surface is placed on the ground, more or less horizontally, said elongate handle means extends substantially upwardly, most conveniently at around 10 to 30 degrees from the vertical,
15 so that in use a dog owner does not have to bend over to any great extent when holding the deployed device.

Advantageously the distance between the deposition surface and any faecal matter thereon and a hand grip portion of the elongate handle means of the collector device according to
20 both aspects of the invention is maximised so as to reduce as far as possible the risk of any faecal matter contained within the receptacle coming into contact with a user.

Preferably said deposition surface when in said deployed state has a diameter of from 5cm to 30cm desirably 10cm to
25 20cm, though it will be appreciated that the size and shape required will depend to a large extent on the size of the dog and of the faecal deposits generally produced by it. Various shapes of deposition surface may be used for example circular, oval, triangular or sectoral.

30 Most preferably with an inflatable collector device according to one aspect of the invention said device comprises a single elongate inflatable tube defining said elongate handle means and the support means of said receptacle, the end portions of said elongate inflatable
35 tube being disposed adjacent each other and provided with a

valve means. Desirably the security means for safeguarding the contents of a loaded receptacle is in the form of a draw-string which passes through said elongate tube and is connected to said valve means such that when said valve
5 means is removed (to permit deflation of the device after use thereof) the removal of the valve pulls on both ends of said draw string so as to draw in the rim of the receptacle over the deposition surface and thereby enclose any faecal matter supported on said deposition surface.

- 10 Other forms of closure means may include adhesive strips, tabs or ribs; hook and loop type fasteners; or other sealing means formed and arranged for drawing together opposed wall means of the receptacle and/or securing closure panel or
15 preferably, seal in, faecal deposits within said receptacle.

Preferably there is provided at the base of said elongate handle means, adjacent said receptacle, a foot engagement portion for engaging with the underside of a user's foot so as to allow raising of the receptacle rim up from the ground
20 so that when the closure means is operated to draw in the rim of the receptacle, this will close in above the faecal deposit resting on a central portion of the receptacle. Desirably said foot engagement portion has a rough surface formation to provide a more positive grip with the underside
25 of a user's foot so that the engagement portion resists pulling out from under the user's foot when under tension.

Most preferably said foot engagement portion is connected to the base of the elongate means by a more or less short (e.g. 5 cm to 30 cm desirably 10-20 cm) strap portion with a
30 distal end portion upon which a user can place a foot after receipt of a deposit in the receptacle so that upon pulling taut of the elongate handle means the receptacle rim can be raised up above the ground prior to drawing in of the closure means draw string to draw inwardly the receptacle
35 rim to close up the receptacle above the faecal deposit.

Alternatively said receptacle comprises a bag which is deployed from said first collapsed state to said second substantially self supporting state and said receptacle support means is in the form of a resilient loop member
5 which is deployed from a first elongate stored position to a second supporting position for providing support to said bag, said bag being provided with a pocket means or the like underneath its deposition surface, into which pocket means said loop member extends in its deployed supporting
10 position.

Further preferred features and advantage of the present invention will appear from the following detailed description given by way of example of some preferred embodiments illustrated with reference to the accompanying
15 drawings in which:-Fig. 1 is a perspective view of a dog faeces collector device in a rolled up state;
Fig. 2 is a front view of the device shown in Fig. 1 in an inflated self supporting state;
Fig. 3 is a side view of device shown in Fig. 2;
20 Fig. 4 is a side view of the device after use in a semi-deflated state;
Fig. 5 is a side view of a second embodiment of collector device according to the invention; and
Fig. 6 shows two different collapsible elongate handle means
25 for use with the invention.

Reference is first made to Fig. 1 which shows a dog faeces collector device of the invention generally indicated by reference number 1. The device as shown in Fig. 1 is in a rolled up stored state so that it may readily be kept in a
30 dog owner's pocket or the like ready to be inflated.

In more detail and with reference to Fig. 2 which shows the device 1 in an inflated ready to use state the device 1 comprises an elongate tube 2 the two ends 4, 6 of which form an elongate handle portion 8 and rim portion 9 for
35 supporting a receptacle 10. The receptacle 10 comprises the centre portion 12 of the elongate tube 2 arranged generally

arcuately for supporting a bag 14 having an upwardly facing deposition surface 16. The receptacle 10 is angled towards the handle 8 of an angle of about 110° and is supported in that position by a flexible fillet 18 (see also Fig. 3).

5 At the top of the handle 8 a mouthpiece 20 comprising a one-way non-return valve 22 is attached to the tube 2 so that the device 1 may be inflated by a user blowing into the mouthpiece 20. A draw string 24, the first end 26 of which is bonded to the mouthpiece 20, passes around the elongate
10 tube 2 and has its second end 28 bonded to the mouthpiece 20. The handle portion 8 has three flexible locating rings 29 arranged for locating a stick or the like (not shown) so as to provide additional rigidity to the handle 8 if required, for example in windy conditions.

15 As shown in Fig. 3, the device 1 has a foot engagement strap 30 which sticks out of the back of the device 1 so to provide a means for holding down the device while operating the draw string 24.

With reference to Fig. 4, once a dog has defecated into the
20 receptacle 10 the mouthpiece 20 is withdrawn whilst the user holds down the device 1 by placing their foot on the foot engagement strap 30. As the mouthpiece is withdrawn air contained within the tube 2 escapes out of the end (shown by arrows A) and the device 1 deflates whilst at the same time
25 the draw string 24 draws the centre portion 12 of the tube 2 together so to cover over the contents 32 of the bag 14 sealing them inside so that a user may safely and hygienically, dispose of the device 1 and the contents. It will be understood that in this way the contents of the bag
30 are kept well away from a user holding the now limp handle 8.

The embodiment shown in Fig. 5 is generally the same as the embodiment described above with reference to Figs. 1 to 4 except that no inflatable handle portion 8 is included. The
35 elongate tube 2 is arranged generally arcuately for

supporting the bag 14 and has an aperture 34 which may have a variety of fittings for example bayonet, screw, friction push fit etc. (not shown) for easy connection to and disconnection from a support member. The elongate tube 2 is
5 provided with an abutment 36 so that the bag 14 may be disengaged from a support member by a users foot without the need to bend over once valve 20 has been removed and the draw string has been operated to seal the bag 14.

It will be appreciated that various modifications may be
10 made to the above described embodiments without departing from the scope of the present invention. Thus for example the elongate handle portion 8 shown in Figs. 1 and 2 may comprise a single elongate tube 2 or a plurality of elongate tubes 2 in side by side relation. Also said handle portion
15 could be provided with a longitudinally extending resilient strip which has a coiled form in its unbiased state for holding the handle in a highly compact pocketable condition in the collapsed state of the handle, and which uncoils upon inflation of the elongate handle means.

20 In the second embodiment shown in Fig. 5 the support member may be of any suitable type including for example a walking stick. Preferably though said support member is collapsible to at least some extent e.g. telescopic or snapable plastic strip which is coilable.

25 Fig. 6 shows two different embodiments of collapsible elongate handle means which could be used as an alternative to the inflatable member described above with reference to Figs. 1 to 4 or as a support member for use with the embodiment described with reference to Fig. 5.

30 Fig. 6(a) shows a telescopic rigid member 38 in a collapsed state. The member 38 comprises four sleeves 40 gradually decreasing in diameter, each respective sleeve being slidable within another sleeve in generally known manner so as to provide a member 38 of variable length. A receptacle
35 10 (only partly shown) is connected to one end of the member

38.

Fig. 6(b) shows an alternative arrangement for the rigid member 38. The member 38 comprises several (only three shown) member elements 40 each connected to an adjacent member element at a hinge 42. Each member element 40 increases in length in a direction away from the receptacle 10 (only partly shown) such that at each hinge 42 the longer of two adjacent member elements 40 overlaps 44 on the underside of the adjacent shorter member element so as to provide support thereto and similarly along the length of the member 10 such that the whole member is supported by each adjacent member element and for supporting the receptacle 10. The member elements 40 are arranged so that the shorter element folds onto the next adjacent longer element shown by arrow 'a' and so forth along the member 38 shown by arrows 'b' and 'c' so that the member can be folded up into a collapsed state.

CLAIMS

1. An animal faeces collector device (1) comprising a collapsible elongate handle means (8) provided at a distal end with a receptacle (10) having an upwardly facing
5 deposition surface (16) in a deployed condition of the device (1) for receiving a faecal deposit (32) thereon, said elongate handle means (8) being formed and arranged so as to be collapsible into a highly compact pocketable form in a collapsed state of the device (1), and to be deployable to a
10 substantially self-supporting state in a deployed state of the device (1).
2. An animal faeces collector device (1) as claimed in claim 1 wherein said receptacle (10) for receiving faecal deposits (32) is itself deployable from a substantially
15 collapsed state to a substantially self-supporting deployed state defining said upwardly facing deposition surface (16) in said deployed state of the device for receiving faecal deposits (32) thereon.
3. An inflatable animal faeces collector device (1) which
20 device comprises a structure deployable from a first highly compact pocketable collapsed state to a second substantially self supporting state defining and supporting a receptacle (10) having an upwardly facing deposition surface (16) in a deployed condition for receiving a faecal deposit (32)
25 thereon, said device (1) having coupling means (34) formed and arranged for coupling with a generally rigid elongate handle means for supporting said device (1) at a distal end thereof, whereby, in use, said device may be inflated, coupled with a said more or less rigid elongate handle means
30 and said receptacle (10) positioned under a dog in the defecating position for the collection of faecal deposits (32).
4. A collector device (1) as claimed in any one of claims 1 to 3 wherein said device (1) includes remotely operable
35 receptacle security means (24) formed and arranged for safeguarding the contents (32) of a loaded receptacle (10).

5. A collector device (1) as claimed in claim 4 wherein said remotely operable receptacle security means (24) comprises a closure means in the form of a drawstring formed and arranged with said elongate handle means (8) and said
5 receptacle (10) for drawing in, over the contents (32) of said receptacle (10), a rim portion (9) thereof.

6. A collector device (1) as claimed in any one of claims 1, 2 and 4 to 5 when dependent on claim 1 wherein said elongate handle means (8) is formed and arranged so as to be
10 inflatable from said collapsed state to said substantially self-supporting state.

7. A collector device (1) as claimed in any one of claims 1 to 6 wherein said receptacle (10) is provided with a support means (9) formed and arranged so as to be inflatable from a
15 said collapsed state of the device to a said substantially self supporting state of the device (1) and to support said receptacle (10) in an open condition in said deployed state of the device (1).

8. A collector device (1) as claimed in claim 1, 2 or any
20 one of claims 4 to 7 when dependent on claim 1 wherein said elongate handle means (8) and said receptacle (10) are formed and arranged so as to be substantially flexible for coilable rolling up into said highly compact pocketable form.

25 9. A collector device (1) as claimed in any one of claims 1 to 8 wherein said elongate handle means (8) or coupling means therefor and said deposition surface (16) are orientated with respect to each other so that when said deposition surface (16) is placed on the ground more or less
30 horizontally, said elongate handle means (8) extends generally vertically upwardly.

10. A collector device (1) as claimed in claim 1, 2 or any one of claims 4 to 9 when dependent on claim 1 wherein said device (1) has a single elongate inflatable tube (2)

defining said elongate handle means (8) and a support means (9) for said receptacle (10), the end portions (4, 6) of said elongate inflatable tube (2) being disposed adjacent each other and provided with a valve means (20).

5 11. A collector device (1) as claimed in any claim 1, 2 or one of claims 4 to 10 when dependent on claim 1 wherein there is provided proximal the base of said elongate handle means (8), or the coupling means therefor, a foot engagement portion (30) for engaging with the underside of a user's
10 foot.


12. A collector device (1) as claimed in claim 1, 2 or any one of claims 4 to 11 when dependent on claim 1, wherein said elongate handle means (8) is provided with a resiliently deformable strip which in a normal rest position
15 tends to adopt a substantially coiled form whereby said handle means is uncoilable from said collapsed state to said deployed condition.

13. A collector device (1) as claimed in claim 1, 2 or any one of claims 4 to 11 when dependent on claim 1, wherein
20 said elongate handle means (8) comprises a plurality of discrete elongate portions interconnected end-to-end and formed and arranged for articulation with respect to an adjacent portion, each portion extending partly under the underside of an adjacent portion so as to provide a
25 cantilevered support thereto.

14. A collector device (1) as claimed in claim 1, 2 or any one of claims 4 to 11 when dependent on claim 1 wherein said elongate handle means (8) comprises a plurality of portions telescopically interconnected so as to be extendible from
30 said collapsed state to said deployed condition.

15. A collector device (1) as claimed in any one of claims 1 to 14 wherein said receptacle is provided with a resilient loop member deployable from a first stored position to a second supporting position for providing support to said
35 receptacle.

1-2



2-2




FIG. 6a




FIG. 6b

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/GB 95/02033

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A01K23/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A01K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR,A,2 444 752 (LADISLAS POLYA) 18 July 1980 see the whole document ---	1, 2, 13, 14
X	DE,U,92 08 882 (WALTHER) 29 October 1992 see figures 1-5 ---	1, 14
X	DE,A,28 04 553 (KARBANGE) 9 August 1979 see figures 1, 2, 6 -----	1, 14

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

9 November 1995

Date of mailing of the international search report

27. 11. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

von Arx, V

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 95/02033

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2444752	18-07-80	NONE	
DE-U-9208882	29-10-92	NONE	
DE-A-2804553	09-08-79	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.